

1/12/06



PATENT APPLICATION

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of	:	David Stanley FENTON and Barry David FENTON
Serial no.	:	10/720,367
Filed	:	November 24, 2003
For	:	FELLER BUNCHER
Group Art Unit	:	3725
Examiner	:	Bena B. MILLER
Docket	:	THOLAM P216US

MAIL STOP ISSUE FEE

The Commissioner for Patents
U.S. Patent & Trademark Office
P. O. Box 1450
Alexandria, VA 22313-1450

SUBMISSION OF CERTIFIED COPY

Dear Sir:

A claim for priority is hereby made under the provisions of 35 U.S.C. § 119 for the above-identified United States Patent Application based upon Canada Patent Application No. 2,422,987 filed March 20, 2003. A certified copy of said Canada application is enclosed herewith.

In the event that there are any fee deficiencies or additional fees are payable, please charge the same or credit any overpayment to our Deposit Account (Account No. 04-0213).

Respectfully submitted,

Michael J. Bujold, Reg. No. 32,018

Customer No. 020210

Davis & Bujold, P.L.L.C.

Fourth Floor

500 North Commercial Street

Manchester NH 03101-1151

Telephone 603-624-9220

Facsimile 603-624-9229

E-mail: patent@davisandbujold.com



Office de la propriété
intellectuelle
du Canada

Un organisme
d'Industrie Canada

Canadian
Intellectual Property
Office

An Agency of
Industry Canada

*Bureau canadien
des brevets
Certification*

*Canadian Patent
Office
Certification*

La présente atteste que les documents
ci-joints, dont la liste figure ci-dessous,
sont des copies authentiques des docu-
ments déposés au Bureau des brevets.

This is to certify that the documents
attached hereto and identified below are
true copies of the documents on file in
the Patent Office.

Specification and Drawings, as originally filed, with Application for Patent Serial No:
2,422,987, on March 20, 2003, by **DAVID STANLEY FENTON and BARRY DAVID
FENTON** for "Feller Buncher".

**CERTIFIED COPY OF
PRIORITY DOCUMENT**

Sylvie Lévesque
Agent certificateur/Certifying Officer

December 8, 2005

Date

Canada

(CIPO 68)
31-03-04

OPIC  CIPO

ABSTRACT OF THE DISCLOSURE

A feller buncher includes an elongate support having an axis, a first side, a second side, a first end and a second end. A first tree receiving cavity is positioned along the first side of the support. A second tree receiving cavity is positioned along the second side of the support. A circular saw is positioned at the second end of the support. The plane of the saw is transverse to the axis of the vertical support. Movable grapple arms are positioned on each of the first side and the second side of the support above the circular saw. The grapple arms are adapted to hold trees while they are being felled and then maintain bunches of felled trees in each of the first tree receiving cavity and the second tree receiving cavity.

TITLE OF THE INVENTION:

Feller Buncher

FIELD OF THE INVENTION

5 The present invention relates to a feller buncher used in the logging industry to fell and then simultaneously bunch together trees.

BACKGROUND OF THE INVENTION

10 United States Patents 5,975,166 (MacLennan 1999) and 6,374,877 (Willey 2002) are examples of feller bunchers. Each of these feller bunchers has an elongate support. A saw is positioned at a bottom of the support, with the plane of the saw transverse to the axis of the support. Grapples are
15 positioned above the saw. The grapples hold individual trees as they are being felled and hold several felled trees against the support to form a bunch.

SUMMARY OF THE INVENTION

20 The present invention relates to a new configuration of feller buncher which has some functional advantages over existing feller buncher configurations.

25 According to the present invention there is provided a feller buncher which includes an elongate support having an axis, a first side, a second side, a first end and a second end. A first tree receiving cavity is positioned along the first side of the support. A second tree receiving cavity is positioned along the second side of the support. A circular
30 saw is positioned at the second end of the support. The plane of the saw is transverse to the axis of the vertical support. Movable grapple arms are positioned on each of the first side and the second side of the support above the circular saw. The grapple arms are adapted to hold trees

while they are being felled and then maintain bunches of felled trees in each of the first tree receiving cavity and the second tree receiving cavity.

The innovation of having a first tree receiving cavity along the first side of the support and a second tree receiving cavity along the second side of the support, provides a number of advantages. One advantage is that trees may be more readily felled from either the first side or the second side of the feller buncher. Another advantage relates to the operation of the circular saw. Having two tree receiving cavities results in two sides of the circular saw being used, rather than just the center area of the saw. This serves to double the capacity of the saw. It also enables a smaller diameter of saw blade to be used.

Although beneficial results may be obtained through the use of the feller buncher, as described above, even more beneficial results may be obtained when a rigid horn is centrally positioned between the first tree receiving cavity and the second tree receiving cavity adjacent to the second end of the support. The rigid horn projects outwardly from the support and can be used for such tasks as clearing debris or lining up logs in a pile.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other features of the invention will become more apparent from the following description in which reference is made to the appended drawings, the drawings are for the purpose of illustration only and are not intended to in any way limit the scope of the invention to the particular embodiment or embodiments shown, wherein:

FIGURE 1 is a perspective view of a feller buncher constructed in accordance with the teachings of the present

invention.

FIGURE 2 is a top plan view of the feller buncher illustrated in **FIGURE 1**, in the process of felling a tree.

FIGURE 3 is a side elevation view of the feller buncher illustrated in **FIGURE 1**, in the process of using the horn to line up logs in a pile.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

10 The preferred embodiment, a feller buncher generally identified by reference numeral 10, will now be described with reference to **FIGURES 1** through 3.

Structure and Relationship of Parts:

15 Referring to **FIGURE 1**, feller buncher 10 includes an elongate support 12 having an axis 14, a first side 16, a second side 18, a first end 20 and a second end 22. Referring to **FIGURE 2**, a first tree receiving cavity 24 is positioned along first side 16. A second tree receiving
20 cavity 26 is positioned along second side 18. Referring to **FIGURE 1**, a circular saw 28 is positioned at second end 22 of elongate support 12 such that the plane of circular saw 28 is in transverse relation to axis 14. Moveable grapple arms 30 are positioned on each of first side 16 and second side 18,
25 above circular saw 28. Elongate support is further adapted with a rigid horn 32 positioned adjacent to second end 22. Referring to **FIGURE 2**, rigid horn 32 is centrally positioned between first tree receiving cavity 24 and second tree receiving cavity 26. Although not part of the inventive
30 concept, referring to **FIGURE 1**, feller buncher is shown attached to a tractor 34 by way of hydraulic arms 36 as illustrated in **FIGURE 3**. Referring to **FIGURES 2** and 3, trees 38 are illustrated.

Operation:

The use and operation of feller buncher 10 will now be described with reference to **FIGURES 1** through **3**. Referring to **FIGURE 1**, in the illustrated embodiment, tractor 34 transports and manipulates feller buncher 10. It will be appreciated that other means of transport and manipulation may be used. Referring to **FIGURE 2**, a user may position either first tree receiving cavity 24 or second tree receiving cavity 26 such that circular saw 28 engages a tree 38. The selection of which of first tree receiving cavity 26 or second tree receiving cavity 28 is used is based upon the best opportunity and orientation that the user may come upon to fell a tree. In the illustrated embodiment, tree 38 is positioned within first tree receiving cavity 24. Once positioned, moveable grapple arms 30 enclose (as shown in dotted lines) tree 38 in receiving cavity 24, grasping and holding tree 38 while circular saw 28 cuts it. Once cutting is finished, tree 38 continues to be held by moveable grapple arms 30, as feller buncher 10 is positioned and manipulated by tractor 34 to cut other trees until a bunch of trees has been accumulated. The bunches of trees may then be left in a pile. Referring to **FIGURE 3**, rigid horn 32 may be projected into a pile of trees 38 in order to sort them and arrange them in piles.

In this patent document, the word "comprising" is used in its non-limiting sense to mean that items following the word are included, but items not specifically mentioned are not excluded. A reference to an element by the indefinite article "a" does not exclude the possibility that more than one of the element is present, unless the context clearly requires that there be one and only one of the elements.


It will be apparent to one skilled in the art that

modifications may be made to the illustrated embodiment without departing from the spirit and scope of the invention as hereinafter defined in the Claims.

**THE EMBODIMENTS OF THE INVENTION IN WHICH AN EXCLUSIVE
PROPERTY OR PRIVILEGE IS CLAIMED ARE DEFINED AS FOLLOWS:**

- 5 1. A feller buncher, comprising:
an elongate support having an axis, a first side, a
second side, a first end and a second end;
a first tree receiving cavity positioned along the first
side of the support;
10 a second tree receiving cavity positioned along the
second side of the support;
a circular saw positioned at the second end of the
support, the plane of the saw being transverse to the axis of
the vertical support; and
15 movable grapple arms positioned on each of the first
side and the second side of the support above the circular
saw, the grapple arms being adapted to hold trees while they
are being felled and then maintain bunches of felled trees in
each of the first tree receiving cavity and the second tree
20 receiving cavity.
2. The feller buncher as defined in Claim 1, wherein a rigid
horn is centrally positioned between the first tree receiving
cavity and the second tree receiving cavity adjacent to the
25 second end of the support, the rigid horn projecting
outwardly from the support.

FIG. 1






FIG. 3

